

APPENDIX 1: MICRO/LEVEL 6-26 SERIES LEVELING SCREW CHART

MICRO/LEVEL® & MXL FOOT THICKNESS & LEVELING SCREW SPECIFICATIONS																				
Leveling Screw Model	For Foot Thickness Up To:									Leveling Screw Specifications						Lock Nut		Washer		
	Micro/Level Isolator Series									Pitch & Length			Head Height	Flat Thickness	Radius at End	Flat Thickness	Thick-ness	Dia-meter	Thick-ness	
	6	8	9	10	14	216	16	20	25/26	Dia.	TPI	Length								
.375C4	2.4									0.375	-16	4	0.22	0.563	3	0.81	0.33	0.56	0.06	
.375C6	4.4								6											
.5M3	1.3									0.50	-13	3	0.38	0.375	3	0.75	0.44	1.06	0.09	
.5M4	2.3								5											
.5M5	3.3								8											
.5M8	6.3									0.625	-11	4	0.38	0.438	3	0.94	0.55	1.31	0.09	
.625M4	2.2	1.5	1.0						5											
.625M5	3.2	2.5	2.0						6											
.625M6	4.2	3.5	3.0						8											
.625M8	6.2	5.5	5.0						10											
.625M10	8.2	7.5	7.0							0.75	-10	4	0.38	0.5	3	1.13	0.42	1.47	0.14	
.75M4		1.5	1.1	0.9					6											
.75M6		3.5	3.1	2.9					8											
.75M8		5.5	5.1	4.9					10											
.75M10		7.5	7.1	6.9						1.00	-14	4	0.50	0.75	3	1.50	0.55	2.00	0.14	
1M4		1.4	1.0	0.8					5											
1M5		2.4	2.0	1.8					6											
1M6		3.4	3.0	2.8		1.7			8											
1M8		5.4	5.0	4.8		3.7			10											
1M10		7.4	7.0	6.8		5.7			12											
1M12		9.4	9.0	8.8		7.7			14											
1M14		11.4	11.0	10.8		9.7				1.125	-12	6	0.50	0.75	6	1.69	0.61	2.25	0.14	
1.125M6			2.9	2.7		1.7	1.7		8											
1.125M8			4.9	4.7		3.7	3.7		10											
1.125M10			6.9	6.7		5.7	5.7		12											
1.125M12			8.9	8.7		7.7	7.7			1.25	-12	6	0.50	7/8	6	1.88	0.72	2.50	0.16	
1.25M6			2.6	1.4	1.5	1.5			8											
1.25M8			4.6	3.4	3.5	3.5			10											
1.25M10			6.6	5.4	5.5	5.5			12											
1.25M12			8.6	7.4	7.5	7.5				1.50	-12	7	0.75	1.125	6	2.25	0.84	3.50	0.19	
1.5M7			3.4	2.3	2.4	2.4	1.8		8											
1.5M8			4.4	3.3	3.4	3.4	2.8		10											
1.5M10			6.4	5.3	5.4	5.4	4.8		12											
1.5M12			8.4	7.3	7.4	7.4	6.8		14											
1.5M14			10.4	9.3	9.4	9.4	8.8		16											
1.5M16			12.4	11.3	11.4	11.4	10.8			1.75	-12	8	0.75	1.25	6	2.75	0.97	4.00	0.21	
1.75M8				3.1	3.2	3.2	2.7		10											
1.75M10				5.1	5.2	5.2	4.7		12											
1.75M12				7.1	7.2	7.2	6.7		14											
1.75M14				9.1	9.2	9.2	8.7			2	-12	8	0.75	1.5	12	3.13	1.09	4.50	0.21	
2M8				3.0		3.1	2.6		10											
2M10				5.0		5.1	4.6		12											
2M12				7.0		7.1	6.6		14											
2M14				9.0		9.1	8.6			2.25	-12	7	1.00	1.75	12	3.50	1.20	4.75	0.25	
2.25M7						2.0	1.4		8											
2.25M8						3.0	2.4	1.9	10											
2.25M10						5.0	4.4	3.9	12											
2.25M12						7.0	6.4	5.9	14											
2.25M14						9.0	8.4	7.9		2.5	-12	8	1.00	1.875	12	3.88	1.45	5.00	0.25	
2.5M8							2.2	1.6	10											
2.5M10							4.2	3.6	12											
2.5M12							6.2	5.6	14											
2.5M14							8.2	7.6		2.75	-12	10	1.00	2.375	12	4.25	1.58	5.50	0.33	
2.75M10							4.0	3.4	12											
2.75M12							6.0	5.4	14											
2.75M14							8.0	7.4		3	-12	10	1.00	Spanner	12	Round	1.70	5.50	0.33	
3M10								3.3	12											
3M12								5.3	14											
3M14								7.3		3.5	-12	10	1.00	Spanner	12	Round	3.5	not supplied		
3.5M10								1.8	12											
3.5M12								3.8	14											
3.5M14								5.8												

NOTES:

Not all Leveling Screw Models listed are stocked.
Custom Lengths are available.

NOTE: Data subject to change without notice.

03/29/2019

